

Fiber Optic Telecommunications

Seppo Honkanen
Micro and Nanosciences Laboratory
Helsinki University of Technology
E-mail: seppo.honkanen@tkk.fi

1

Fiber Optic Telecommunications
TUT, March 2007

Outline

Basic Properties of Optical Fibers

- What is an optical fiber ?



Modern Optical Communication System

- How does it work ?
- Advantages of fiber optics


2

Fiber Optic Telecommunications
TUT, March 2007

Refraction of Light

Refractive index:

$$n = \frac{C_{\text{vacuum}}}{C_{\text{material}}}$$




3

Fiber Optic Telecommunications
TUT, March 2007

Total Internal Reflection

Snell's law:

$$n_{\text{glass}} \cdot \sin I = n_{\text{air}} \cdot \sin R$$



Critical angle $A \sim 41.8^\circ$


4

Fiber Optic Telecommunications
TUT, March 2007

Light Guiding by a Water Jet

Total Internal Reflection can confine light in a material denser than its surroundings

Daniel Colladon (Swiss physicist), 1841



Fiber Optic Telecommunications
TUT, March 2007


5

Optical Fibers

No Cladding: light leaks out



Cladding prevents leaking





$$n_{core} > n_{clad} > n_{air}$$

Fiber Optic Telecommunications
TUT, March 2007

6

Optical Fibers




Fiber Optic Telecommunications
TUT, March 2007

7

Fiber Cable

Cross Section: Deep-Sea Submarine Cable



Fiber Optic Telecommunications
TUT, March 2007

8

Attenuation in Optical Fibers

Fiber Attenuation

Measured in decibels: $\text{dB} = -10\log_{10}(P_{\text{out}}/P_{\text{in}})$

Loss values


- Fibers made of standard glass:
1000 dB/km, $\sim 10^{-100} \%$ ($\sim 90\%$ per meter)
- Plastic fibers: 100 dB/km ($\sim 90\%$ per 100 meters)
- Silica fibers: 0.2 dB/km Less than 5% per km !

9

Fiber Optic Telecommunications
TUT, March 2007

Attenuation vs. Wavelength

Signal Wavelength ~ 1.55 microns



10

Fiber Optic Telecommunications
TUT, March 2007

Fabrication of Optical Fibers

Fabrication of silica fibers by a two-step process

1. Preform fabrication
 - Modified Chemical Vapor Deposition (MCVD) Method
 - Outside Vapor Deposition (OVD) Method
 - Vapor-phase Axial (VAD) Method
2. Drawing into an optical fiber

Fabrication of multi-component glass fibers


1. Single-step double-crucible method
2. Rod-in tube method
 - 1. Preform fabrication
 - 2. Drawing into an optical fiber

11

Fiber Optic Telecommunications
TUT, March 2007

The core of a silica based fiber can have a purity of better than 0.1 ppb (parts per billion (10^{-9})). Such high degree of purity has been made possible by Chemical Vapor Deposition (CVD) techniques originally developed for Semiconductor Industry. The method uses the difference in the vapor pressures of the liquid metal halides of the material and those of the impurities.

Vapor pressures for metal halides and potential impurities





12

Fiber Optic Telecommunications
TUT, March 2007

Modified Chemical Vapor Deposition (MCVD)

A chemical reaction takes place inside a silica tube with the aid of a H_2/O_2 burner outside the tube. The metal halide vapors are oxidized and small glass particles, called “soot”, are deposited on the inside wall of the tube.



Purified oxygen gas is bubbled into reservoirs containing liquid metal halides, at a prescribed pressure and temperature.




Fiber Optic Telecommunications
TUT, March 2007

13

Fiber Drawing


In the second step of the process, an optical fiber is drawn from the preform rod. The lower end of the preform is heated in a furnace to $\sim 2000\text{--}2100^\circ\text{C}$ (melting temperature is $\sim 1900^\circ\text{C}$). The fiber diameter is controlled by the pulling speed. Feedback signal from the fiber diameter measurement controls the pulling speed.



Fiber Optic Telecommunications
TUT, March 2007

14

Loss spectrum of a single-mode fiber produced in 1979:




(T. Miya et al., Electron. Lett. **15**, 106, 1979)

Fiber Optic Telecommunications
TUT, March 2007

15

In 2000 Lucent scientists published a study on spatial distribution of OH concentration in fiber preforms. The concentration was found to increase with increasing distance from the center of the preform. Based on some new diffusion modeling and their experiments, they concluded that water enters the preform rod from the outside of the rod and diffuses into the molten, flowing glass much faster than what was earlier extrapolated from low temperature measurements. So to make “dry” fibers, they simply changed the $\text{O}_2\text{--H}_2$ torch to a dry heat source, such as O_2 plasma torch.

Loss and dispersion of the Lucent’s Dry “AllWave” fiber:



(G. A. Thomas et al., Nature **404**, 262, 2000)

Fiber Optic Telecommunications
TUT, March 2007

16

Why Optical Fibers ?

Some Advantages

- Light weight
- Immune to EM-interference
- Nearly impossible to tap

17

Fiber Optic Telecommunications
TUT, March 2007

Key Advantages

- Attenuation is independent of the modulation speed
- Ultra-High Carrier Frequency
 - $f \sim 190 \text{ THz @ } 1.55 \mu\text{m wavelength}$
(1 Trillion Hz = 10^{12} Hz)

18

Fiber Optic Telecommunications
TUT, March 2007

Attenuation: Fiber vs. copper


Coaxial Cable

Loss depends strongly on frequency

Optical Fiber

Loss does not depend on frequency


High speed transmission possible !!




19

Fiber Optic Telecommunications
TUT, March 2007

Fiber Optic Telecommunications



Digital Transmission: at speeds as high as **10 or 40 Gbit/sec**



20

Fiber Optic Telecommunications
TUT, March 2007

Importance of the Carrier Frequency ?

Higher the carrier frequency




Greater the systems' transmission capacity (bandwidth)

21

Fiber Optic Telecommunications
TUT, March 2007


The Electromagnetic Spectrum



22

Fiber Optic Telecommunications
TUT, March 2007


Modulation frequency higher than the carrier frequency ?



23

Fiber Optic Telecommunications
TUT, March 2007

Modulation




24

Fiber Optic Telecommunications
TUT, March 2007

Fiber Optics


- Fundamentally nearly unlimited bandwidth !!
 - Carrier frequency ~ 190 THz



Fiber Optic Telecommunications
TUT, March 2007

25

Dense Wavelength Division Multiplexing (DWDM)




Fiber Optic Telecommunications
TUT, March 2007

26

Erbium Doped Fiber Amplifier (EDFA)

- The key enabler of DWDM systems
- Gain through stimulated emission in an Er^{3+} -doped single-mode fiber





Fiber Optic Telecommunications
TUT, March 2007

27

Glass Waveguides on Si

- Three silicon oxynitride layers on a thick silicon substrate (1.3 mm)
- Film deposition with PECVD technique ($n \approx 1.48$, $\Delta n \approx 0.008$)
- Two layer masking process
- Plasma etching of the waveguide core

Microscope image with visible light:



Fiber Optic Telecommunications
TUT, March 2007

28

State-of-the-Art DWDM

Example:

Distance: 1200 km
 Number of wavelengths: 125
 Total capacity: 5 Tbit/s

How much is 1 Tbit/s?

- 10 million phone calls
- hundreds of thousands of TV channels

29

Fiber Optic Telecommunications
TUT, March 2007


Qwest's North-American Fiber-Optic Backbone System



30


Fiber Optic Telecommunications
TUT, March 2007

Qwest's Global Fiber-Optic Network



31

Fiber Optic Telecommunications
TUT, March 2007



32

Fiber Optic Telecommunications
TUT, March 2007

Submarine Fiber-optic System

Fiber Manufacturing / System Assembly / Cable Laying

